



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. NICKEL PL. 100 MIN THICK OVER COPPER STRIKE  
 3. PHOSPHOR BRONZE PER QQ-B-750  
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 5. TEFLON MIL-P-1946B  
 6. JIS H 3250, C 2700

- 1. CRIMPED FERRULE  
HEX CRIMP SIZE .213"
- 2. CRIMPED CONTACT PIN  
HEX CRIMP SIZE .100"

REVISIONS					DIMENSIONS ARE IN MILLIMETERS				PART NO. N6521A1-NT3G-1A-50		<b>Amphenol</b>	
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE			UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE		
					0.5-6	= ±0.2				10-11-01'	N PANEL CRIMP JACK	
					6-30	= ±0.4			CHECKED	DATE		
					30-120	= ±0.6				10-11-01'	DRAWING NO.	
					120-315	= ±1			DRAWN	DATE	KJ-N6521A1-NT3G-223U-50	
					315-1000	= ±1.6				10-11-01'	ITEM NO.	
					1000-2000	= ±2.4						
5	FERRULE	NOTE 6	NOTE 2	1	FR-635/56X127	SCALE	2/1	ISSUE	A	FILE NO.		
4	CONTACT PIN	NOTE 3	NOTE 4	1	N7000-4-3/1							
3	BARREL	NOTE 1	NOTE 2	1	N5000-3-427/31							
2	INSULATOR	NOTE 5	NATURAL	1	N5000-4T-50-A							
1	BODY	NOTE 1	NOTE 2	1	N6521A1-15							